


## Cable glands Progress® ultraFLAT stainless steel A2



### Entry thread metric

- One-piece sealing insert
- not overall length insulated

|                       |                                                    |
|-----------------------|----------------------------------------------------|
| <b>Article no:</b>    | <b>1040.17.96.30.080</b>                           |
| EAN:                  | 7611614264721                                      |
| Front part            | CrNi stainless steel A2 (DIN EN 1.4305 / AISI 303) |
| Push-down nut         | Nickel-plated brass                                |
| Seal                  | FKM                                                |
| Sealing washer        | FKM                                                |
| Operation temperature | -40°C / +200°C                                     |
| Strain relief         | Version A acc. to EN 62444                         |
| Wall thickness        | max. 5 mm                                          |
| Protection class      | IP 68 (up to 10 bar) / IP 69                       |
| Entry thread          | M16x1.5                                            |
| Clamping range min.   | 6.5 mm                                             |
| Clamping range max.   | 8.0 mm                                             |
| Wrench size           | 19 mm                                              |
| Diameter A            | 22 mm                                              |
| Dimension H           | 4.0 mm                                             |
| Thread length L       | 21 mm                                              |
| Note                  | 1                                                  |
| Dispatch              | 25                                                 |

1 = Available on request  
FDA-cleared sealings