
Cable glands Progress® EMC nickel-plated brass with contact sleeve







Short entry thread Pg

Type approval: Progress MS EMV

- One-piece sealing insert
- · not overall length insulated

Article no:	1080.09.100
EAN:	7611614115054
Material	Nickel-plated brass
Contact sleeve	Nickel-plated brass
Seal	TPE
O-ring	NBR
Operation temperature	-40°C / +100°C
Protection class	IP 68 (up to 10 bar) / IP 69
NEMA Type rating	4X
Properties	Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland
Entry thread	Pg 9
Clamping range min.	8.0 mm
Clamping range max.	10.0 mm
Wrench size	18 mm
Dimension H	25 mm
Thread length L	6 mm
Dispatch	50
Operation temperature Protection class NEMA Type rating Properties Entry thread Clamping range min. Clamping range max. Wrench size Dimension H Thread length L	-40°C / +100°C IP 68 (up to 10 bar) / IP 69 4X Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland Pg 9 8.0 mm 10.0 mm 18 mm 25 mm 6 mm

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

