


## Cable glands Progress® EMC powerCONNECT nickel-plated brass



### Short entry thread metric

#### Type approval: Progress EMV powerCONNECT

- Two-piece sealing insert
- not overall length insulated

<b>Article no:</b>	<b>1084.80.650</b>
EAN:	7611614312651
Material	Nickel-plated brass
Seal	TPE
O-ring	NBR
Operation temperature	-60°C / +100°C
Strain relief	Version A acc. to EN 62444
Protection class	IP 68 (up to 10 bar) / IP 69
NEMA Type rating	4X
Properties	For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design
Entry thread	M80x2.0
Clamping range with insert min.	- mm
Clamping range with insert max.	- mm
Clamping range without insert min.	58.0 mm
Clamping range without insert max.	65.0 mm
Cable shield diameter	62.0
Inner diameter	59.8 mm
Wrench size	95 mm
Dimension H	58 mm
Thread length L	12 mm
Additional note	1
Dispatch	1

1 = One-piece sealing insert

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

#### Available on request:

- Stainless steel A2 or A4
- Entry thread Pg and NPT