

## Cable glands Progress® stainless steel A2



### Long entry thread Pg

- Two-piece sealing insert
- not overall length insulated

|                                    |                                                    |
|------------------------------------|----------------------------------------------------|
| <b>Article no:</b>                 | <b>1100.13.94</b>                                  |
| EAN:                               | 7611614134093                                      |
| Material                           | CrNi stainless steel A2 (DIN EN 1.4305 / AISI 303) |
| Identification                     | 1 groove                                           |
| Seal                               | TPE                                                |
| O-ring                             | NBR                                                |
| Operation temperature              | -40°C / +100°C                                     |
| Protection class                   | IP 68 (up to 10 bar) / IP 69                       |
| Entry thread                       | Pg 13                                              |
| Clamping range with insert min.    | 8.0 mm                                             |
| Clamping range with insert max.    | 11.0 mm                                            |
| Clamping range without insert min. | 11.0 mm                                            |
| Clamping range without insert max. | 15.0 mm                                            |
| Wrench size                        | 24 mm                                              |
| Dimension H                        | 21 mm                                              |
| Thread length L                    | 10 mm                                              |
| Dispatch                           | 50                                                 |

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.