


## Cable glands Progress® stainless steel A2



### Long entry thread metric

#### Type approval: Progress S2

- One-piece sealing insert
- not overall length insulated

|                       |                                                    |
|-----------------------|----------------------------------------------------|
| <b>Article no:</b>    | <b>1100.25.94.205</b>                              |
| EAN:                  | 7611614133621                                      |
| Material              | CrNi stainless steel A2 (DIN EN 1.4305 / AISI 303) |
| Identification        | 1 groove                                           |
| Seal                  | TPE                                                |
| O-ring                | NBR                                                |
| Operation temperature | -40°C / +100°C                                     |
| Strain relief         | Version A acc. to EN 62444                         |
| Protection class      | IP 68 (up to 10 bar) / IP 69                       |
| Entry thread          | M25x1.5                                            |
| Clamping range min.   | 16.0 mm                                            |
| Clamping range max.   | 20.5 mm                                            |
| Wrench size           | 30 mm                                              |
| Dimension H           | 25 mm                                              |
| Thread length L       | 11 mm                                              |
| Dispatch              | 25                                                 |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.