## One-gang junction box - ECON® Iso +













## One-gang junction box - ECON® Iso +

- · Sealing lip on all sides
- · 4 swivel cutters
- · 4 screw domes
- · with 2 device screws +/-
- · including centering aid
- · including setting tool (Art. No.1090-22) per packaging unit

| Article no:                         | 1159-55       |
|-------------------------------------|---------------|
| EAN:                                | 4013456549302 |
| Depth                               | 55 mm         |
| for insulation thicknesses          | > 60 mm       |
| Cut hole Ø                          | 68 mm         |
| Device screws                       | 2             |
| Screw spacing                       | 60 mm         |
| Cable entries of up to Ø 11.5 mm    | 4             |
| Conduit entries M20                 | 4             |
| Support connectors for each package | 5             |
| Protection class                    | IP 30         |
| Glow wire                           | 850 °C        |
| Halogen-free                        | Yes           |
| Packaging inner/dispatch            | 10/100        |

The ECON® Iso + one-gang junction box is the solution for electrical installation work in wood fibre insulation boards. Four swivels, specially designed for use in solid heat insulation and plaster base boards, ensure secure anchoring – also for retrofitting! The ECON® technology elastic sealing membrane guarantees air tightness and allows the toolless insertion of conduits or cables. This means that switches, sockets, intercoms and many more can be installed permanently and securely and heat bridge-free.

- · Air-tight and heat bridge-free electrical installation in accordance with DIN 18015-5
- · Suitable for pressure-resistant insulation panels of 60 mm thickness and greater
- · 4 swivels for secure mechanical anchoring
- · Making of combinations is possible









