

# AGRO Adapter Progress® nickel-plated brass with integrated cable gland



CUK  
PA

## Long entry thread Pg

### Type approval: Progress MS Adapter

- Two-piece sealing insert
- overall length insulated

|                                    |                                                               |
|------------------------------------|---------------------------------------------------------------|
| <b>Article no:</b>                 | <b>1165.13</b>                                                |
| EAN:                               | 7611614141794                                                 |
| Material                           | Nickel-plated brass                                           |
| Seal                               | TPE                                                           |
| O-ring                             | NBR                                                           |
| Operation temperature              | -40°C / +100°C                                                |
| Protection class                   | Cable gland IP 68                                             |
| Note                               | The max. clamping range depends on the conduit inner diameter |
| Thread outside                     | Pg 13                                                         |
| Internal thread                    | Pg 13                                                         |
| Clamping range with insert min.    | 8.0 mm                                                        |
| Clamping range with insert max.    | 11.0 mm                                                       |
| Clamping range without insert min. | 11.0 mm                                                       |
| Clamping range without insert max. | 14.5 mm                                                       |
| Wrench size                        | 24 mm                                                         |
| Dimension H                        | 36 mm                                                         |
| Thread length L                    | 10 mm                                                         |
| Dispatch                           | 25                                                            |

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.