


# AGRO Adapters Progress® nickel-plated brass with integrated EMC cable gland



## Long entry thread metric

### Type approval: Progress MS Kombi EMC

- One-piece sealing insert
- not overall length insulated

|                                    |  |
|------------------------------------|--|
| <b>Article no:</b>                 | <b>1165.80.63.500</b>  |
| EAN:                               | 7611614149387  |
| Material                           | Nickel-plated brass  |
| Contact sleeve                     | Nickel-plated brass  |
| Seal                               | TPE  |
| O-ring                             | NBR  |
| Operation temperature              | -40°C / +100°C   |
| Strain relief                      | Version A acc. to EN 62444   |
| Protection class                   | Cable gland IP 68  |
| Note                               | -  |
| Properties                         | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Thread outside                     | M63x1.5  |
| Internal thread                    | M63x1.5  |
| Clamping range without insert min. | 46.0 mm  |
| Clamping range without insert max. | 50.0 mm  |
| Wrench size                        | 70 mm  |
| Dimension H                        | 59 mm  |
| Thread length L                    | 14 mm  |
| Dispatch                           | 5  |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.