


## AGRO combination EMC conduit gland for copper braidings



### Entry thread metric

- Suitable for ROHRflex® corrugated tubings

|                                    |                                                                                                                                                                                                    |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Article no:</b>                 | <b>1165.84.63.54</b>                                                                                                                                                                               |
| EAN:                               | 7611614219653                                                                                                                                                                                      |
| Material                           | Nickel-plated brass                                                                                                                                                                                |
| Contact sleeve                     | Nickel-plated brass                                                                                                                                                                                |
| O-ring                             | NBR                                                                                                                                                                                                |
| Operation temperature              | -40°C / +120°C                                                                                                                                                                                     |
| Protection class                   | IP 68 (together with Rohrflex® corrugated tube)                                                                                                                                                    |
| Properties                         | Copper braidings may be terminated without any problem with our combination EMC conduit gland. A contact bushing grants optimal shield contact at the same time vibration-proof leading of cables. |
| Entry thread                       | M63x1.5                                                                                                                                                                                            |
| Clamping range without insert min. | 25.0 mm                                                                                                                                                                                            |
| Clamping range without insert max. | 45.0 mm                                                                                                                                                                                            |
| Wrench size                        | 70 mm                                                                                                                                                                                              |
| Dimension H                        | 49 mm                                                                                                                                                                                              |
| Thread length L                    | 14 mm                                                                                                                                                                                              |
| Dispatch                           | 5                                                                                                                                                                                                  |