Prefix® concrete construction box for fixing to the reinforcement



- · One-gang junction box for fixing to the reinforcement
- Can be used for concrete coverings from 20 60 mm
- · Pre-fixing by means of Prefix® installation technology
- · 1-piece with moulded front and rear part
- · Standardised combination distance 71 mm
- with 4 screw domes and 2 expanding claw fields
- Art. No. 1211-01 replaces Art. No. 1211-61



1211-01
4013456550957
290 mm
78 mm
91 mm
60 mm
2
4
2
8
25/50

The new Prefix® concrete construction boxes, in addition to the proven product features such as lateral installation clamps for fastening to the reinforcement, mounting clips for pre-fixing the items and marked wave profile for an exact and secure fit, now also have innovative conduit entries, insertion options in the rear part of the box as well as separators that can be broken out at a later date for connecting devices in combinations.

- Quick and easy installation on the opposing formwork, without support element and abutment
 Spacers to the side formwork ensure full circulation of the concrete and allow exposed concrete
- installations in passage and edge areas
- · Suitable for 20 60 mm concrete covers
- Innovative conduit entries with diameters of 25/32 mm and 20/25 mm, for quick fitting on the construction site
- · Insertion options up to 25 mm diameter on the rear base of the box
- · Easy manual assembly
- · Sturdy signal bristle and bold colouring for easy retrieval in the concrete surface
- · Large inlay and installation clearance
- Easy installation of pre-wired installation accessories in multiple combinations using a bridge that can be broken off afterwards



