

## Prefix® universal support



### Prefix® universal support

- For electrical installations on the opposing formwork side.
- Facilitates fixing to the reinforcement
- Adjustable to concrete ceilings 20, 25, 30 or 35
- Pre-fixing by means of Prefix® installation technology
- Can be used for the following articles:
- End and transition bushes / item no. 1261-82/-83/-84
- Wall and ceiling transitions 30° / item no. 1261-92/-93/-94
- Wall and ceiling transitions 90° / item no. 1261-95/-96/-97

Article no:	1261-00
EAN:	4013456552357
Length	87 mm
Width	45 mm
Height	36 mm
Number of parts	1
for concrete covers	20, 25, 30, 35 mm
Dispatch	350

The Prefix® universal support enables simple, fast fitting of electrical installations in solid wall elements on the opposing formwork side without a support element for the steel formwork table. The support can be easily adjusted to the required concrete ceiling by means of a snap-in connection and attached to the new end and transition bushes, wall and ceiling transitions 30° and wall and ceiling transitions 90° by means of a snap-in connection. The previously customary and costly in-house constructions using timber blanks can thus be dispensed with, disruptions to the further production process are a thing of the past and production of a good wall surface quality is guaranteed without restriction.

- For overhead electrical installations in prefabricated solid walls without support elements
- With integrated dimension indication, easily adjustable to the common concrete ceilings 20 mm, 25 mm, 30 mm or 35 mm
- Generous tolerance compensation for fixing to the reinforcement
- Prefixing using Prefix® installation technology leaves both hands free for fixing with tie wires

