

## B<sup>2</sup> conduit connectors



### Conduit transition coupling Ø 32 mm

- For toolless connection of Ø 32 mm conduits to the B<sup>2</sup> one-gang junction boxes 1262-XX and 1263-XX
- Accepts rigid and flexible conduits
- Damping of conduit vibrations during the compaction process
- Prevents the conduits from penetrating the B<sup>2</sup> one-gang junction boxes and thus avoids subsequent conduit shortening

<b>Article no:</b>	<b>1263-32</b>
EAN:	4013456586864
DIN EN conduit Ø	32 mm
Dispatch	100

The range of B<sup>2</sup> conduit connectors offers a secure and toolless conduit connection to the B<sup>2</sup> one-gang junction boxes without the need for special tools. The conduit connection created using a conduit connector is absolutely impermeable to concrete and safely dampens the vibrations of the conduits during the compaction process. As the conduit connection is made outside the B<sup>2</sup> one-gang junction boxes, no conduit protrudes into the interior of the box, thus eliminating the need to shorten the conduit on the inside. With the new 90° conduit connectors, sideways conduit connections can now also be easily implemented in narrow installation areas.

- Toolless conduit connection, no special tools required
- Precisely fitting "variable" conduit connection, absolutely sealed against concrete
- Damping of vibrations during the high-frequency or low-frequency compression process
- Conduit connection outside the one-gang junction box, no conduits protruding into the interior of the box
- Conduit connectors 90° for the lateral connection of conduits in narrow installation areas

