

## KompaX® 2 concrete installation housing



### KompaX®2 housing for slab ceilings with mineral fibreboard

- for factory fitting
- for variable ceiling cut-outs up to 180 mm
- installation height for built-in luminaires or loudspeakers max. 100 mm
- consists of front ring, assembled mineral fibreboard and rear part
- for ceilings of 18 cm total thickness upwards
- incl. support elements for installation heights 100/150/200 mm

<b>Article no:</b>	<b>1292-28</b>
EAN:	4013456533233
Length	470 mm
Width	290 mm
Depth	131 mm
Ceiling exit (CE) Ø	0-180 mm
LED wattage max.	45 Watt
Lamp wattage max.	52 Watt
Dispatch	10

KompaX® 2 housing system for fitted downlights and loudspeakers in concrete ceilings with wide range of accessories for almost all applications. Height-adjustable using intermediate frames. The various front parts make it extremely practical.

- Housing system for fitted downlights and loudspeakers
- For in-situ or prefabricated concrete
- For precise installation openings from Ø 100–200 mm
- For device installation depths up to 200 mm\*
- For ceiling thicknesses from 180–300 mm\*
- Tolerance compensation during slab ceiling installation

Replacement mineral fibreboard (not illustrated)  
Art. No. 1292-98

