

Air-tight flush-mounting boxes



UPPLUS



LUFTDICHT



One-gang junction box ECON® 15, air-tight, with device screws, Depth 66 mm

- Air-tight design with ECON® sealing membranes
- dimensions in accordance with German DIN 49073
- For M20/M25 conduits and cables

Article no:	1556-21
EAN:	4013456533851
Depth	66 mm
Screw spacing	60 mm
Number of screw domes	4
Splayed claw fields	2
Tool-free cable and conduit entries in the connector area up to M25	2
Tool-free cable and conduit entries up to 11 mm below the connector	2
Tool-free cable and conduit entries up to M25 around the box	4
Tool-free cable and conduit entries up to 11 mm around the box	4
Device screws	2
Air-tight	Yes
Halogen-free	Yes
Packaging inner/dispatch	25/250

Flush-mounting boxes with ECON® technology permit guaranteed air-tight installation. They offer a variety of options for air-tight conduit and cable entries and can be either plastered or processed using Klemmfix®. The new ECON® Multi-Membrane allows the insertion of several cables without gusset formation or the insertion of conduits up to M25.

- Air-tight design with ECON® sealing membranes
- Avoids leaks in exterior facades made from hollow chamber blocks
- Variable and tool-free cable and conduit entries
- Torsion-proof, guaranteed standardised combination distance of 71 mm

