

UP¹ ECON® electronics box and UP¹ ECON® two-gang junction box





- · With guick fixing for installation without plaster
- · With 6 x 3 screw domes
- · Side-neutral combination
- · Many through-wiring possibilities
- · Standardised combination distance 71 mm

Article no:	1656-26
EAN:	4013456590335
Length	149 mm
Width	80 mm
Depth	68 mm
Drill hole Ø	2 x 82 mm
With depth stop	Yes
With quick-fixing (also suitable for PU foam)	Yes
Screw spacing	60 mm
Number of screw domes	6 x 3
Device screws	4
Tool-free cable entries close to the floor up to \varnothing 11 mm in the combination area	3
Tool-free line and pipe entries in the combination range up to M25	3
Toolless cable and conduit entry into box shells up to M25	3
Toolless cable and conduit entry into box shells up to M32	2
Toolless cable entries up to Ø 11 mm in the bottom of the box	4
Toolless pipe entries up to M25 in the box bottom	2
Halogen-free	Yes
Air-tight Air-tight	Yes
Packaging inner/dispatch	10/100



- · With quick fixing for installation without plaster
- · Elastic sealing membrane for guaranteed air-tightness
- · Variable and tool-free insertion of cables and DIN EN conduits up to M32
- Additional space for decentral installation of KNX / LON UP actuators, flush-mounted cut-off relays for Venetian blinds, and many more
- · Separator wall for standardised fitting of two voltage types in one box
- · Maintenance of cable bending radii for network connection boxes optimal data transfer
- · Easy installation of pre-wired accessories and multi-media connection boxes













