

# AGRO combination conduit glands Progress® nickel-plated brass with integ



CUK  
PA

## Long entry thread Pg

### Type approval: Progress MS Kombi

- Connector for tubing with AD mm
- Two-piece sealing insert
- overall length insulated

|                                    |                                                               |
|------------------------------------|---------------------------------------------------------------|
| <b>Article no:</b>                 | <b>1710.60.09.14</b>                                          |
| EAN:                               | 7611614144450                                                 |
| Material                           | Nickel-plated brass                                           |
| Seal                               | TPE                                                           |
| O-ring                             | NBR                                                           |
| Operation temperature              | -40°C / +100°C                                                |
| Protection class                   | Cable gland IP 68                                             |
| Note                               | The max. clamping range depends on the conduit inner diameter |
| Entry thread                       | Pg 9                                                          |
| Outer diameter                     | 14 mm                                                         |
| Clamping range with insert min.    | 6.0 mm                                                        |
| Clamping range with insert max.    | 8.0 mm                                                        |
| Clamping range without insert min. | 8.0 mm                                                        |
| Clamping range without insert max. | 10.5 mm                                                       |
| Wrench size                        | 18/21 mm                                                      |
| Dimension H                        | 38 mm                                                         |
| Thread length L                    | 10 mm                                                         |
| Dispatch                           | 50                                                            |

Depending on the type of conduit, the stabilising bush must be ordered separately.  
Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.