

## Optical termination outlet (OTO), flush-mounting



### Optical termination outlet (OTO), partial equipped

- Scope of delivery: OTO, 1x SC/APC DX coupler

<b>Article no:</b>	<b>4250002</b>
EAN:	4013456577855
Network level	4
Installation type	Flush-mounting
Protection class	IP20
Impact resistance	IK07
Number of fibers	1 - 4
Number of splice trays	1
Halogen-free	Yes
Loop length (splice tray)	150
Bending radius (splice tray)	25 mm
Splice protection holder	CSP Crimp / Mini heat shrink tubing
Number of cable entries	1
Temperature range storage	-10 °C / +60 °C
Temperature range installation	-10 °C / +60 °C
Temperature range during operation	-20 °C / +60 °C
Coupler   Type	SC/APC Duplex
Coupler   Art	Without flange, SC Duplex footprint
Coupler   Amount	1
Coupler   Sleeve material	Ceramic, slotted
Coupler   Housing material	plastic, halogen-free, flame-retardant
Coupler   Laser and dust protection	Integrated protection cap, blind plug
Coupler   Insertion Loss	≤ 0,20 dB
Coupler   Mating cycles	1000
Dispatch	10

The optical termination outlet will be the termination point of the optical fiber cable within the appartement / home. At this stage the connection to the optical network termination will be realized via an optical patch cable, as well as to the further individual network connections via WLAN/LAN for example.

- Installation in all KAISER one-gang junction boxes
- Partial equipped and splice ready availabel
- Overlength management
- Suitable for CSP (Crimp-Splice protection)
- Design-compatible with all common TAE covers

