

Optical termination outlet (OTO), surface-mounted



Optical termination outlet (OTO), partial equipped

· Scope of delivery: OTO, 2x LC/APC DX coupler

Article no:	4252004
EAN:	4013456578456
Length	85 mm
Width	85 mm
Height	16 mm
Network level	4
Installation type	Surface mount
Protection class	IP20
Impact resistance	IK07
Number of fibers	1 - 4
Number of splice trays	1
Halogen-free	Yes
Loop length (splice tray)	250
Bending radius (splice tray)	25 mm
Splice protection holder	CSP Crimp / Mini heat shrink tubing
Number of cable entries	3
Cabel entry Ø	2,3 - 5,3 mm
Temperature range storage	-10 °C / +60 °C
Temperature range installation	-10 °C / +60 °C
Temperature range during operation	-20 °C / +60 °C
Colour	Signal white (RAL 9003)
Coupler LC/APC Duplex	with flange, SC Simplex footprint
Coupler Amount	2
Coupler Sleeve material	Ceramic, slotted
Coupler Housing material	plastic, halogen-free, flame-retardant
Coupler Laser and dust protection	Integrated protection cap, blind plug
Coupler Insertion Loss	≤ 0,20 dB
Coupler Mating cycles	1000
Dispatch	50

The optical termination outlet will be the termination point of the optical fiber cable within the appartement / home. At this stage the connection to the optical network termination will be realized via an optical patch cable, as well as to the further individual network connections via WLAN/LAN for example.

- Compact fibre-optic subscriber connection
- unequipped, partial equipped and splice ready availabel
- Overlength management
- Suitable for CSP (Crimp-Splice protection)
- Integrated strain relief

