

Patch cable, LC-APC-LC-APC SX, G.657.A2, LSZH, yellow



Patch cable, LC/APC-LC/APC SX, G.657.A2, LSZH, yellow, 5.0 m

· Scope of delivery: patch cable, LC/APC-LC/APC SX

Article no:	4263005
EAN:	4013456582163
Cable length	5,0 m
Certificate	GHMT Channel Link (z7479a-22 ; c7479a-22)
Network level	4
Fibre optic line Fibre optic class	Single Mode OS2 (G.657.A2)
Fibre optic line LC/APC simplex connectors	2x (Grade B)
Fibre optic line Fibre optic type	EasyBand® Plus-Mini 200µm Reduced Diameter Bending Insensitive Fibre
Fibre optic line Fibre optic color coding	yellow
Fibre optic line Stranding element	Aramid Garn
Fibre optic line Material	LSZH
Fibre optic line Cable Ø	2,00 mm +/- 0,15 mm
Fibre optic line Minimum bend radius	50 mm (Installation), 7,5 mm (Permanent)
Fibre optic line Temperature range storage	-10 °C / +60 °C
Fibre optic line Temperature range installation	0 °C / +50 °C
Fibre optic line Temperature range during operation	-10 °C / +60 °C

High-quality fibre optic patch cable with pre-assembled LC/APC connector (LC/APC-LC/APC SX, G.657.A2, LSZH). Available in 5 different cable lengths for precise application.

- 5 different cable lengths
- Single Mode OS2 (G.657.A2)
- Patch cable Ø 2.00 +/- 0.15 mm
- LC/APC connector with dust protection