O-range ECON® 2 / 3 / 4 - gang junction boxes



LUFTDICHT

O-range ECON® 3 one-gang junction box, air-tight, Depth 48 mm

- Air-tight design with sealing membranes
- Toolless cable and conduit entires
- Integrated cable retention of the NYM cable, self-locking of the conduit
- Standardised separation of individual installation openings using a bridge
- Can be combined with all O-range® programme applications

Article no:	**9253-22**
EAN:	4013456550902
For panel thickness	7 - 40 mm
Depth	48 mm
Cut hole Ø	3 x 68 mm
Centre distance	71 mm
Number of installation device openings	3
Number of bridges	1
Device screws +/-	6
Conduit entries up to Ø 20 mm	6
Conduit entries up to Ø 25 mm	2
Cable entries 3 x 1.5 mm²	2
Cable entries 3 x 2.5 mm² or 5 x 1.5 mm²	2
Packaging inner/dispatch	5/50

With the new O-range ECON® 2 / 3 / 4 - gang junction boxes, KAISER offers the perfect basis and especially easy processing for the fitting of all standard installation accessories in multiple combinations. Thanks to their large installation opening without a central separation, it is easy to wire multiple devices together and even makes possible the use of pre-wired installation accessories. If different electrical circuits – e. g. for supply and communication connections – are used within a combination, the individual accessory installation spaces can be separated easily and in a standardised way.

- Easy installation of pre-wired accessories without spatial separation
- Maximum flexibility when fixing accessories, generous tolerance compensation
- Standardised separation of individual installation openings using a bridge
- Complete assembly and installation with just one screwdriver
- Can be combined with all O-range® programme applications

O·range ECON® air-tight IP 30 850 °C INNOVATION