

Air-tight cavity wall installation



LUFTDICHT



O-range ECON® 63 one-gang box, air-tight, Depth 49 mm

- Air-tight design with sealing membranes
- Fully insulated, air-tight through-wiring for combinations using support connectors
- Toolless cable or conduit entries
- Integrated cable retention of NYM cables, self-locking of conduits

| | |
|--|----------------|
| Article no: | 9263-22 |
| EAN: | 4013456537606 |
| For panel thickness | 7 - 40 mm |
| Depth | 49 mm |
| Cut hole Ø | 68 mm |
| Device screws | 2 |
| Tube entries up to M25 | 2 |
| Cable entries 3 x 2.5 mm ² or 5 x 1.5 mm ² | 2 |
| Cable entries 3 x 1.5 mm ² | 2 |
| Support connectors for each package | 7 |
| Air-tight | Yes |
| Packaging inner/dispatch | 25/250 |

Air-tight O-range® cavity wall boxes with ECON® technology for energy-efficient electrical installation according to GEG. The elastic ECON® technology sealing membrane allows air-tight electrical installation.

- Elastic sealing membrane for guaranteed air-tightness
- Innovative clamp technology with integrated cable retention
- Toolless cable and conduit entry
- Air-tight combined with support connector

O-range ECON®

