

Installation housing O-range ECON® Universal 120



Installation housing O-range ECON® Universal 120, air-tight, Depth 65 mm

- With universal screw-on surface for mounting accessories and installation accessories
- For individual round and cornered installation openings
- Air-tight design with sealing membranes
- Toolless cable or conduit entries
- Integrated cable retention of NYM cables, self-locking of conduits

| | |
|--|----------------|
| Article no: | 9273-50 |
| EAN: | 4013456581869 |
| Depth | 65 mm |
| For panel thickness | 7 – 40 mm |
| Cut hole Ø | 120 mm |
| max. opening size Ø | 100 mm |
| max. square opening size Ø | 75 x 75 mm |
| max. luminaire installation diameter | 86 mm |
| For devices with an installation depth of max. | 50 mm |
| max. lamp output LED | 8 Watt |
| Conduit entries up to Ø 25 mm | 6 |
| Cable entries 3 x 1.5 mm ² | 6 |
| Cable entries 3 x 2.5 mm ² or 5 x 1.5 mm ² | 6 |
| Cable entries 5 x 2.5 mm ² or 7 x 1.5 mm ² | 4 |
| Air-tight | Yes |
| Dispatch | 10 |

With the new O-range ECON® Universal 120 installation housing, KAISER offers maximum flexibility on the construction site. In addition to the wiring for an entire room unit, the installation of various accessories or installation accessories is also possible. If necessary, the universal fastening and screw-on surface can be opened to the desired extent, thus ensuring clean installation of recessed luminaires, smoke detectors and much more. Particularly easy to install thanks to tool-free cable and conduit entries. The sealing membranes guarantee permanent air tightness and thus energy-efficient electrical installation in accordance with the Building Energy Act (GEG).

- Universal screw-on surface for clean mounting of attachments without drilling or dowelling
- For creating individual installation openings up to Ø 100 mm
- Complete assembly and installation with just one screwdriver
- Toolless cable and conduit entry
- Installation in Ø 120 mm cut hole

