

PROTECT® solid wood fire protection one-gang junction box



Fire protection PROTECT® one-gang junction box for solid wood

- For F30-B to F120-B solid wood elements
- Mounting with rib fixing
- Cable entry enables tolerance compensation of the cable route
- Also for directly opposing installation
- Preserves the sound insulation properties of the solid wood elements

Article no:	9464-05
EAN:	4013456590175
Depth	60 mm
Cut hole Ø	74 mm
Screw spacing	60 mm
Support connectors for each package	5
Sound insulation	Yes
Classification report	Yes
Cable entries of up to Ø 11.5 mm	8
For wall thicknesses of	100 mm
Combination distance by simply removing the pre-embossed edge	71 mm
Halogen-free	Yes
Packaging inner/dispatch	10/100

The new solid wood PROTECT® one-gang junction box has been specially developed for the requirements of installation in solid wood elements. Fastening with ribs and the innovative cable entries ensure optimum and standardised installation in a solid wood element in visible wood quality without additional cutting or effort. Thanks to their arrangement and design, the innovative cable entries ensure flexible cable entry and thus compensate for the installation tolerances that arise when routing cables in the solid wood element. In addition, the PROTECT® solid wood fire protection one-gang junction box maintains the fire resistance of the solid wood element from F30-B to F120-B without the need for additional encapsulation.

- Maintains the F30-B to F120-B fire resistance duration
- For a directly opposing installation
- Toolless installation thanks to rib fixing
- Innovative cable entry enables tolerance compensation of the cable route
- Simple and toolless cable entry up to Ø 11.5 mm
- For installation openings Ø 74 mm
- Preserves the sound insulation properties of the solid wood elements

