

Compact PD and Multi-PD distribution box



Flat box

- This product is designed so that you can assemble it yourself.
- Suitable for mounting in suspended ceilings and underfloor areas
- Break-out openings for M20 cable gland, WAGO WINSTA® MIDI / Wieland gesis® CLASSIC GST18® 3, 4 and 5-pole and BST14.
- WAGO WINSTA® MIDI / Wieland gesis® CLASSIC GST18® 3-, 4- and 5-pole and BST14.

Article no:	AT2525
EAN:	8712259244600
Length	120 mm
Width	120 mm
Depth	40 mm
Max. conductor cross section	4 mm ²
Operation temperature	- 40°C / + 70°C
Protection class	IP40
Rated voltage	400 V
Housing feed-through	Breakout opening
Number of break-out openings	8
Colour	light grey
Halogen-free	Yes
Dispatch	20

The compact PD distribution boxes for connector systems really show off their advantages especially well in electrical installations in confined spaces, such as in raised floors, underfloor systems or suspended ceilings. Thanks to their compact design and low overall height, they cut a slim figure even where space is limited. The prefabricated distribution boxes can be used as a transition from sheathed cables to the pluggable electrical installation or as a 100% pluggable box. Due to the factory pre-wiring, the error potential is practically zero, since only the components / connectors are connected at the installation site via a "click". Versions with 3-, 4- or 5-pole connectors are possible. The distribution boxes of the compact Multi-PD series can be mechanically connected to each other. This easy to lock system means that several boxes can be lined up next to each other so that larger distribution units can also be set up. Additional fixing lugs on the outside of the box offer a practical option for wall or ceiling attachment or fixing to the floor. For the compact PD and Multi-PD distribution boxes, prefabricated distribution boxes for up to 9 outlets as well as empty boxes are available, which can be equipped individually.