

Connecting sleeve

Connecting sleeve, 6 fibres, CSP, 2 outlets

- Scope of delivery: connecting sleeve, 2x cable gland, splice cassette



Article no:	AT29016
EAN:	8712259297781
Network level	4
Installation type	Underground / Aboveground
Protection class	IP68
Chemical resistance	Yes
Vibration strength	Yes
Impact resistance	Yes
Halogen-free	Yes
Number of fibers	6
Number of splice trays	1
Loop length (splice tray)	200
Bending radius (splice tray)	23 mm
Splice protection holder	CSP Crimp / Mini heat shrink tubing
Entry cable/duct	2
Cable / conduit inlet features	Sand / Waterproof
Cable / conduit inlet bending strength	Yes
Cable/duct entry Ø	5,0 – 10,0 mm
Housing closure	Snap-in hook
Temperature range storage	-10 °C / +50°C
Temperature range installation	-10 °C / +50°C
Temperature range during operation	
Length	120 mm
Width	95 mm
Height	55 mm
Colour	grey / orange
Dispatch	5

The connecting sleeve by the KAISER GROUP is suitable for extending or repairing fibre optic cables. Due to the well thought-out design, the fitter can carry out the assembly quickly and without errors.

- Simple assembly
- Time saving due to systematic assembly sequence.
- Compact design