

## Repair sleeve (CFD)



### Repair sleeve CFD, mast 3.0 - 6.5 mm, CSP, HS, IP68

· Scope of delivery: repair sleeve

<b>Article no:</b>	<b>AT29020</b>
EAN:	8712259335230
Network level	3
Installation type	Underground / Aboveground
Protection class	IP68
Chemical resistance	Yes
Vibration strength	Yes
Impact resistance	IK09
Halogen-free	Yes
Execution	Mast, CSP, HS
Number of fibers	2
Number of splice trays	1
Loop length (splice tray)	230
Bending radius (splice tray)	22,5 mm
Splice protection holder	CSP Crimp / Mini heat shrink tubing
Entry cable/duct	2
Cable / conduit inlet features	Sand / Waterproof
Cable / conduit inlet bending strength	Yes
Cable/duct entry Ø	3,0 – 6,5 mm
Housing closure	Rotary lock
Standard	EN 124-1:2015 Group 2
Temperature range storage	-10 °C / +50°C
Temperature range installation	-10 °C / +50°C
Temperature range during operation	-20 °C / +60°C
Length	155 mm
Width	85 mm
Colour	Black / grey
Dispatch	25

The repair sleeve is a proven and robust solution for conveniently and quickly connecting, extending or repairing directly buried fibre optic connection / customer cables both above and below ground. For above-ground installation, the mounting bracket can be used for surface installation.

- Easy and quick installation
- Universally applicable
- Ordered assembly sequence