

Distribution closure underground for fibre management plate (FMP)



Distribution closure, housing underground for FMP, IP68

· Scope of delivery: distribution closure, sand seal

Article no:	AT29030
EAN:	8712259295503
Network level	3
Installation type	Underground
Protection class	IP68
Overlength management	max. 6.000 mm
Chemical resistance	Yes
Vibration strength	Yes
Impact resistance	IK07
Halogen-free	Yes
Entry cable/duct	4
Cable / conduit inlet features	Sandproof
Cable / conduit inlet bending strength	Yes
Cable/duct entry Ø	38 x 7.0 mm, 2 x 14 / 10 mm, buried cables / conduit bundle
Housing closure	Locking
Locate	101.4 kHz detection coil in cover
Standard	EN 124-1:2015 Group 2
Ground cover (min.)	300 mm
Max. installation depth	1,800 mm
Temperature range storage	-10 °C / +60°C
Temperature range installation	-10 °C / +60°C
Temperature range during operation	-20 °C / +60°C
Length	900 mm
Width	350 mm
Height	300 mm
Colour	Black / grey

For the underground branching of cable and conduit systems, the distribution closure is used in combination with the fibre management plate (FMP) by KAISER. The distribution closure has been designed for the greatest possible customer benefit. All fibre management plates (FMP) from KAISER are compatible and can be mounted dust- and waterproof in the housing cover. In addition, the distribution closure has an IP68 protection class and protects the fibre optic splice connections against dirt and water ingress.

- Flexibility in the management of fibre optic networks
- Plug & Play installation
- Flexibility in the FTTB/H concept