

House transfer point (HTP), shutter, ready to splice



House transfer point HTP, 2 fibres, 1 LC/APC DX, ready to splice

- Scope of delivery: HTP with cover, LC/APC duplex coupling, ready to splice

Article no:	AT29245
EAN:	8712259505862
Network level	3
Installation type	Surface mount
Protection class	IP20
Number of fibers	2
Number of splice trays	1
Connector quantity	1
Connector version	LC / APC DX, shutter
Pigtail quantity	2
Pigtail version	LC / APC SX
atene KOM released	Yes
Halogen-free	Yes
Loop length (splice tray)	250
Bending radius (splice tray)	30 mm
Splice protection holder	CSP Crimp / Mini heat shrink tubing
Entry cable/duct	1 × 10,0 mm, 1 × 4,5 mm, 4 × 4,0
Temperature range storage	-10 °C / +60°C
Temperature range installation	-10 °C / +60°C
Temperature range during operation	-20 °C / +60°C
Length	153 mm
Width	91 mm
Height	61 mm
Colour	white
Dispatch	4

The house transfer point is a compact fibre optic termination unit. Mechanical protection (CSP crimp) of the splice connection and easy installation are guaranteed. In addition, the house transfer point has up to 8× SC/simplex, LC/duplex, E2000 coupling breakouts. Different variants of the house transfer point (HTP) have been approved by "atene KOM" for funding projects.

- Compact design
- Simple and safe plug-in connection with plug-in module
- Time saving due to systematic assembly sequence.