

Mains distributor (Gf-NVt) - Cable/conduit break-out opening Ø 5.5 – 10.0 mm



Mains distributor (NVt), 96 fibres, HS, 16 outlets, loop

- Scope of delivery: Gf-NVt, FMB including splice cassettes, 4x stainless steel bolts, sealing material, moisture absorber

Article no:	AT29328
EAN:	8712259542737
Network level	3
Installation type	Oberirdisch
Protection class	IP65
Chemical resistance	Yes
Vibration strength	Yes
Impact resistance	Yes
Halogen-free	Yes
Number of fibers	96
Number of splice trays	8
Height of splice trays	8 mm
Cascadable (loop function)	Yes
Loop length (splice tray)	300
Bending radius (splice tray)	30 mm
Splice protection holder	HS Heat shrink tubing
Entry cable/duct	2
Cable/duct entry Ø	4,5 – 8,3 mm
Number of cable / conduit breakout openings	No
Cable / conduit breakout opening Ø	No
Cable/duct output quantity	16
Cable/duct output Ø	5,5 – 10,0 mm
Fixing possibility	Screw connection
Temperature range storage	-10 °C / +50°C
Temperature range installation	-10 °C / +50°C
Temperature range during operation	-20 °C / +60°C
Length	250 mm
Width	500 mm
Height	1170 mm
Colour	Light grey - RAL 7035

The mains distributor by the KAISER GROUP is suitable for installation in streets or at crossroads. The advantage over underground distribution points is quick and easy access. Subsequent splicing, cable or conduit laying can be carried out without great effort. The splice distributor box with cover has the protection class IP65 and is protected against dust and water ingress.

- Plug & Play installation
- Flexibility in the management of fibre optic networks
- Flexibility in the FTTX concept.