

## Fibre management plate (FMP) - Cable/conduit break-out opening Ø 3,0 – 8,0



### Fibre management plate FMP, 96 fibres, CSP, 48 outlets, loop

- Scope of delivery: FMP including splice cassettes, 4x mounting screws, sealing material, moisture absorber

<b>Article no:</b>	<b>AT29354</b>
EAN:	8712259388038
Network level	3
Installation type	Underground
Protection class (in supply sleeve)	IP68
Halogen-free	Yes
Number of fibers	96
Number of splice trays	8
Height of splice trays	8 mm
Cascadable (loop function)	Yes
Loop length (splice tray)	300
Bending radius (splice tray)	30 mm
Splice protection holder	CSP Crimp / Mini heat shrink tubing
Entry cable/duct	48
Cable/duct entry Ø	4,5 – 8,3 mm
Number of cable / conduit breakout openings	No
Cable / conduit breakout opening Ø	No
Cable/duct output Ø	3,0 – 8,0 mm
Temperature range storage	-10 °C / +60°C
Temperature range installation	-10 °C / +60°C
Temperature range during operation	-20 °C / +60°C
Length	380 mm
Width	220 mm
Height	130 mm
Colour	Transparent / Grey

The innovative product design of the splice distribution box is suitable for installation in the underground distribution point supply sleeve (AT29030). The installation-friendly product design allows simple, fast and thus time-saving assembly.

- Flexibility in the management of fibre optic networks
- Plug & Play installation
- Flexibility in the FTTX concept.