

## Building distributor (Gf-GV) - Cable/conduit break-out opening Ø 3,0 – 8,0 m



### Building distributor Gf-GV, 48 fibres, HS, 24 outlets, loop, IP65

- Scope of delivery: FMB including splice cassettes, 4x mounting screws, sealing material, mounting bracket

<b>Article no:</b>	<b>AT29391</b>
EAN:	8712259374864
Network level	4
Installation type	Surface mount
Protection class	IP65
Halogen-free	Yes
Number of fibers	48
Number of splice trays	4
Height of splice trays	8 mm
Cascadable (loop function)	Yes
Loop length (splice tray)	300
Bending radius (splice tray)	30 mm
Splice protection holder	Heat shrink tubing
Entry cable/duct	2
Cable/duct entry Ø	4,5 – 8,3 mm
Number of cable / conduit breakout openings	2
Cable / conduit breakout opening Ø	M20 / M25
Cable/duct output quantity	24
Cable/duct output Ø	3,0 – 8,0 mm
Temperature range storage	-10 °C / +60°C
Temperature range installation	-10 °C / +60°C
Temperature range during operation	-20 °C / +60°C
Length	380 mm
Width	220 mm
Height	130 mm
Colour	Transparent / Grey

The splice distributor box can be used as a surface-mounted building distributor with the help of the mounting device and cover if required. The splice distributor box with cover (FMB) has protection class IP65 and is protected against dust and water ingress.

- Flexibility in the management of fibre optic networks
- Plug & Play installation
- Flexibility in the FTTX concept.