

## AGRO EMC cable glands Progress® nickel-plated brass with contact sleeve in

**Short entry thread metric****Type approval: Progress MS EMC EX**

- One-piece sealing insert
- not overall length insulated

|                       |  |
|-----------------------|--|
| <b>Article no:</b>    | <b>EX1080.20.110</b>   |
| EAN:                  | 7611614178004  |
| Material              | Nickel-plated brass  |
| Seal                  | TPE  |
| O-ring                | FPM  |
| Operation temperature | -60°C / +100°C   |
| Protection class      | IP 66 / IP 68 (up to 10 bar)   |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31  |
| Gas                   | II 2G Ex eb IIC Gb   |
| Dust                  | II 2D Ex tb IIIC Db  |
| Zone                  | Gas 1 and 2 / dust 21 and 22   |
| Certificate           | SEV 15 ATEX 0152X  |
| IECEx Certificate     | IECEx SEV 15.0019X   |
| CCC Certificate       | CCC 2022322313004811   |
| Properties            | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread          | M20x1.5  |
| Clamping range min.   | 8.0 mm   |
| Clamping range max.   | 11.0 mm  |
| Wrench size           | 24 mm  |
| Dimension H           | 25 mm  |
| Thread length L       | 6 mm   |
| Dispatch              | 50   |

1 = Metric coarse-pitch thread (with VDE test report)

Long entry thread available on request