

AGRO EMC cable glands Progress® nickel-plated brass with contact sleeve in



Short entry thread metric

Type approval: Progress MS EMC EX

- One-piece sealing insert
- not overall length insulated

| | |
|-----------------------|--|
| Article no: | EX1080.40.285 |
| EAN: | 7611614178110 |
| Material | Nickel-plated brass |
| Seal | TPE |
| O-ring | FPM |
| Operation temperature | -60°C / +100°C |
| Protection class | IP 66 / IP 68 (up to 10 bar) |
| Test standard | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas | II 2G Ex eb IIC Gb |
| Dust | II 2D Ex tb IIIC Db |
| Zone | Gas 1 and 2 / dust 21 and 22 |
| Certificate | SEV 15 ATEX 0152X |
| IECEx Certificate | IECEx SEV 15.0019X |
| CCC Certificate | CCC 2022322313004811 |
| Properties | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread | M40x1.5 |
| Clamping range min. | 24.0 mm |
| Clamping range max. | 28.5 mm |
| Wrench size | 46 mm |
| Dimension H | 34 mm |
| Thread length L | 8 mm |
| Dispatch | 10 |

1 = Metric coarse-pitch thread (with VDE test report)

Long entry thread available on request