


AGRO cable glands Progress® EMC Rapid nickel-plated brass with contact dis

**Short entry thread Pg****Type approval: Progress MS EMC Rapid EX**

- One-piece sealing insert
- not overall length insulated

| | |
|-----------------------|---|
| Article no: | EX1081.07.060 |
| EAN: | 7611614211916 |
| Material | Nickel-plated brass |
| Seal | TPE |
| O-ring | FPM |
| Operation temperature | -60°C / +100°C |
| Protection class | IP 66 / IP 68 (up to 10 bar) |
| Test standard | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas | II 2G Ex eb IIC Gb |
| Dust | II 2D Ex tb IIIC Db |
| Zone | Gas 1 and 2 / dust 21 and 22 |
| Certificate | SEV 15 ATEX 0152X |
| IECEx Certificate | IECEx SEV 15.0019X |
| CCC Certificate | CCC 2022322313004811 |
| Properties | For a quick installation of partially dismantled cables as well as thoroughly shielded cables |
| Entry thread | Pg 7 |
| Clamping range min. | 4.5 mm |
| Clamping range max. | 6.0 mm |
| Wrench size | 15 mm |
| Dimension H | 20 mm |
| Thread length L | 6 mm |
| Dispatch | 50 |

Long entry thread available on request