


# AGRO synthetic cable glands Progress® GFK for increased safety Ex e II with



## Entry thread metric

### Type approval: Progress GFK Multi EX

- Light grey RAL 7035
- One-piece sealing insert

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| <b>Article no:</b>    | <b>EX1571.17.4.015</b>                            |
| EAN:                  | 7611614239545                                     |
| Material              | Polyamide glass fiber reinforced                  |
| Properties            | halogen-free                                      |
| Seal                  | TPE / NBR                                         |
| Operation temperature | -20°C / +85°C                                     |
| Protection class      | IP 66 / IP 68                                     |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                   | II 2G Ex eb IIC Gb                                |
| Dust                  | II 2D Ex tb IIIC Db                               |
| Zone                  | Gas 1 and 2 / dust 21 and 22                      |
| Certificate           | SEV 15 ATEX 0152X                                 |
| IECEx Certificate     | IECEx SEV 15.0019X                                |
| CCC Certificate       | CCC 2022322313004811                              |
| Entry thread          | M16x1.5                                           |
| Clamping range min.   | 1.0 mm                                            |
| Clamping range max.   | 1.5 mm                                            |
| Number of cables      | 4                                                 |
| Wrench size           | 21 mm                                             |
| Dimension H           | 26 mm                                             |
| Dimension L           | 12 mm                                             |
| Note                  | 3                                                 |
| Dispatch              | 50                                                |

3 = Material sealing insert NBR  
Suitable locking pins see accessories