

# AGRO cable glands Progress® nickel-plated brass with trumpet and clamps in



## Short entry thread metric

### Type approval: Progress MS T+KB EX

- Two-piece sealing insert
- not overall length insulated

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>Article no:</b>                 | <b>EX1801.17</b>                                  |
| EAN:                               | 7611614175584                                     |
| Material                           | Nickel-plated brass                               |
| Screws                             | Stainless steel A2                                |
| Seal                               | TPE                                               |
| O-ring                             | FPM                                               |
| Operation temperature              | -60°C / +100°C                                    |
| Protection class                   | IP 66 / IP 68 (up to 10 bar)                      |
| Test standard                      | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                                | II 2G Ex eb IIC Gb                                |
| Dust                               | II 2D Ex tb IIIC Db                               |
| Zone                               | Gas 1 and 2 / dust 21 and 22                      |
| Certificate                        | SEV 15 ATEX 0151                                  |
| IECEx Certificate                  | IECEx SEV 15.0018                                 |
| CCC Certificate                    | CCC 2022322313004717                              |
| Entry thread                       | M16x1.5                                           |
| Clamping range with insert min.    | 6.0 mm                                            |
| Clamping range with insert max.    | 8.0 mm                                            |
| Clamping range without insert min. | 8.0 mm                                            |
| Clamping range without insert max. | 10.5 mm                                           |
| Wrench size                        | 18 mm                                             |
| Diameter A                         | 28 mm                                             |
| Dimension H                        | 43 mm                                             |
| Thread length L                    | 5 mm                                              |
| Dispatch                           | 50                                                |