

AGRO EMC cable glands Progress® nickel-plated brass with contact sleeve and

**Short entry thread Pg****Type approval: Progress MS EMC KB EX**

- One-piece sealing insert
- not overall length insulated

Article no:	EX1803.80.07.075
EAN:	7611614176819
Material	Nickel-plated brass
Screws	Stainless steel A2
Seal	TPE
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68 (up to 10 bar)
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0151
IECEx Certificate	IECEx SEV 15.0018
CCC Certificate	CCC 2022322313004717
Entry thread	Pg 7
Clamping range min.	6.0 mm
Clamping range max.	7.5 mm
Wrench size	15/16 mm
Dimension H	26 mm
Thread length L	6 mm
Note	1
Dispatch	50

1 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X_x000D_
Long entry thread available on request