


AGRO cable glands Progress® EMC easyCONNECT with clamps increased safety

**Long entry thread metric****Type approval: Progress MS EMV easyCONNECT KB EX**

- Two-piece sealing insert
- not overall length insulated

Article no:	EX1813.83.12.065
EAN:	7611614326627
Material	Nickel-plated brass
Screws	Stainless steel A2
Seal	TPE
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0151
IECEx Certificate	IECEx SEV 15.0018
CCC Certificate	CCC 2022322313004717
Entry thread	M12x1.5
Clamping range with insert min.	- mm
Clamping range with insert max.	- mm
Clamping range min.	5.0 mm
Clamping range max.	6.5 mm
Wrench size	15/16 mm
Dimension H	31 mm
Dimension L	10 mm
Additional note	1/2
Dispatch	50

1 = One-piece sealing insert

2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X

Available on request:

- Entry thread Pg and NPT
- Executions in steel A2 and A4