
Reduction fittings nickel-plated brass increased safety Ex e II













Accessories

Type approval: Reduktion MS EX

- · Outer thread metric
- · Inner thread metric
- · with O-ring

Article no:	EX3500.25.20
EAN:	7611614175447
Material	Nickel-plated brass
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0151
IECEx Certificate	IECEx SEV 15.0018
CCC Certificate	CCC 2022322313004717
Thread outside	M25x1.5
Internal thread	M20x1.5
Additional note	-
Wrench size	30 mm
Dimension H	3.5 mm
Dimension L	7 mm
Note	-
Dispatch	25
Dimension H Dimension L Note	3.5 mm 7 mm

- 1 = Metric coarse-pitch thread (with VDE test report)
- 2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X

The norm interdicts to screw several reduction/enlarging fittings into each other!

