

## Reduction fittings nickel-plated brass increased safety Ex e II



### Accessories

#### Type approval: Reduktion MS EX

- Outer thread Pg
- Inner thread metric
- with O-ring

|                       |   |
|-----------------------|---|
| <b>Article no:</b>    | <b>EX3500.48.50</b>                               |
| EAN:                  | 7611614176130                                     |
| Material              | Nickel-plated brass                               |
| O-ring                | FPM   |
| Operation temperature | -60°C / +100°C                                    |
| Protection class      | IP 66 / IP 68                                     |
| Test standard         | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                   | II 2G Ex eb IIC Gb                                |
| Dust                  | II 2D Ex tb IIIC Db                               |
| Zone                  | Gas 1 and 2 / dust 21 and 22                      |
| Certificate           | SEV 15 ATEX 0151                                  |
| IECEx Certificate     | IECEx SEV 15.0018                                 |
| CCC Certificate       | CCC 2022322313004717                              |
| Thread outside        | Pg 48   |
| Internal thread       | M50x1.5   |
| Additional note       | -   |
| Wrench size           | 65 mm   |
| Dimension H           | 5.5 mm  |
| Dimension L           | 11 mm   |
| Note                  | -   |
| Dispatch              | 5   |

1 = Metric coarse-pitch thread (with VDE test report)

2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X

The norm interdicts to screw several reduction/enlarging fittings into each other!